## **AMENDMENTS TO THE CLAIMS**

No claim is amended. A complete listing of the claims is provided below.

1. (Previously Presented) A method of performing physiological gating in a medical procedure, comprising:

acquiring a sequence of images, the sequence of images comprises at least a first image and a second image of a target region, wherein one of the first and second images is a real-time image;

determining a first composite image based on the first and second images; and gating a medical procedure based on the first composite image.

- 2. (Original) The method of claim 1, wherein the determining comprises subtracting the first image from the second image.
- 3. (Original) The method of claim 1, further comprising determining a first value associated with a contrast of the first composite image.
- 4. (Original) The method of claim 3, wherein the gating the medical procedure is performed based at least on the first value.
- 5. (Original) The method of claim 4, wherein the gating comprises de-activating a radiation beam when the first value is above a prescribed threshold value.

- 6. (Original) The method of claim 1, wherein the medical procedure comprises a radiation treatment procedure.
- 7. (Original) The method of claim 1, further comprising: acquiring a third image of the target region; determining a second composite image based on the second and third images; and gating the medical procedure based on the second composite image.
- 8. (Original) The method of claim 1, wherein the sequence of images are fluoroscopic images.
- 9. (Original) The method of claim 1, wherein the sequence of images are real-time images created during a session.
- 10. (Previously Presented) A system for performing physiological gating in a medical procedure, comprising:

means for acquiring a sequence of images, the sequence of images comprises at least a first image and a second image of a target region, wherein one of the first and second images is a real-time image;

means for determining a first composite image based on the first image and the second image; and

means for gating a medical procedure based on the first composite image.

- 11. (Original) The system of claim 10, further comprising means for determining a first value associated with a contrast of the first composite image.
- 12. (Original) The system of claim 11, wherein the means for gating the medical procedure performs the gating based at least on the first value.
- 13. (Original) The system of claim 12, wherein the means for gating comprises means for deactivating a radiation beam when the first value is above a prescribed threshold value.
- 14. (Original) The system of claim 10, wherein the medical procedure comprises a radiation treatment procedure.
- 15. (Previously Presented) A computer readable medium having a set of stored instructions, the execution of which causes a process to be performed, the process comprising:

acquiring a sequence of images, the sequence of images comprises at least a first image and a second image of a target region, wherein one of the first and second images is a real-time image;

determining a first composite image based on the first and second images; and gating a medical procedure based on the first composite image.

- 16. (Original) The computer readable medium of claim 15, wherein the determining comprises subtracting the first image from the second image.
- 17. (Original) The computer readable medium of claim 15, wherein the process further comprising determining a first value associated with a contrast of the first composite image.
- 18. (Original) The computer readable medium of claim 17, wherein the gating the medical procedure is performed based at least on the first value.
- 19. (Original) The computer readable medium of claim 18, wherein the gating comprises deactivating a radiation beam when the first value is above a prescribed threshold value.
- 20. (Original) The computer readable medium of claim 15, wherein the medical procedure comprises a radiation treatment procedure.
- 21. (Original) The computer readable medium of claim 15, wherein the process further comprising:

acquiring a third image of the target region;

determining a second composite image based on the second and third images; and gating the medical procedure based on the second composite image.

- 22. (Original) The computer readable medium of claim 15, wherein the sequence of images are fluoroscopic images.
- 23. (Original) The computer readable medium of claim 15, wherein the sequence of images are real-time images created during a session.
- 24. (Previously Presented) A method of performing a medical procedure, comprising: providing a plurality of templates, each of the templates having an image and treatment data, wherein the treatment data comprises radiation treatment data;

acquiring an input image;

registering the input image with one of the templates; and

performing a medical procedure based on the treatment data of the one of the templates
that is registered with the input image.

- 25. (Original) The method of claim 24, wherein the registering comprises selecting a template from the plurality of templates that best matches an image in the input image.
- 26. (Original) The method of claim 24, further comprising enhancing a moving object in the input image.
- 27. (Original) The method of claim 26, wherein the enhancing comprises determining a composite image of previously acquired input images.

6

- 28. (Original) The method of claim 27, wherein the determining a composite image comprises performing an image averaging on the previously acquired input images.
- 29. (Original) The method of claim 27, wherein the enhancing further comprises subtracting the composite image from the input image.
- 30. (Canceled)
- 31. (Previously Presented) The method of claim 24, wherein the radiation treatment data comprises one or a combination of beam-on signal, beam-off signal, beam-on duration, beam shape data, and dosage data.
- 32. (Original) The method of claim 24, wherein the medical procedure comprises directing a radiation beam to an object.
- 33. (Original) The method of claim 32, wherein the performing the medical procedure comprises adjusting a delivery of the radiation beam based on the treatment data.
- 34. (Previously Presented) A system for performing a medical procedure, comprising:

  means for providing a plurality of templates, each of the templates having an image and treatment data, wherein the treatment data comprises radiation treatment data;

7

means for acquiring an input image;

means for registering the input image with one of the templates; and

means for performing a medical procedure based on the treatment data of the one of the
templates that is registered with the input image.

- 35. (Original) The system of claim 34, wherein the means for registering comprises means for selecting a template from the plurality of templates that best matches an image in the input image.
- 36. (Original) The system of claim 34, further comprising means for enhancing a moving object in the input image.
- 37. (Original) The system of claim 34, wherein the radiation treatment data comprises one or a combination of beam-on signal, beam-off signal, beam-on duration, beam shape data, and dosage data.
- 38. (Original) The system of claim 34, wherein the means for performing a medical procedure comprises means for directing a radiation beam to an object.
- 39. (Original) The system of claim 38, wherein the means for directing a radiation beam comprises means for adjusting a delivery of the radiation beam based on the treatment data.

40. (Previously Presented) A computer readable medium having a set of stored instructions, the execution of which causes a process to be performed, the process comprising:

providing a plurality of templates, each of the templates having an image and treatment data, wherein the treatment data comprises radiation treatment data;

acquiring an input image;

registering the input image with one of the templates; and

performing a medical procedure based on the treatment data of the one of the templates that is registered with the input image.

- 41. (Original) The computer readable medium of claim 40, wherein the registering comprises selecting a template from the plurality of templates that best matches an image in the input image.
- 42. (Original) The computer readable medium of claim 40, wherein the process further comprising enhancing a moving object in the input image.
- 43. (Original) The computer readable medium of claim 42, wherein the enhancing comprises determining a composite image of previously acquired input images.
- 44. (Original) The computer readable medium of claim 43, wherein the determining a composite image comprises performing an image averaging on the previously acquired input images.

9

- 45. (Original) The computer readable medium of claim 43, wherein the enhancing further comprises subtracting the composite image from the input image.
- 46. (Original) The computer readable medium of claim 40, wherein the radiation treatment data comprises one or a combination of beam-on signal, beam-off signal, beam-on duration, beam shape data, and dosage data.
- 47. (Original) The computer readable medium of claim 40, wherein the medical procedure comprises directing a radiation beam to an object.
- 48. (Original) The computer readable medium of claim 47, wherein the performing the medical procedure comprises adjusting a delivery of the radiation beam based on the treatment data.
- 49. (Original) A method of performing physiological gating in a medical procedure, comprising:

providing a template;

acquiring an input image of a target region;

registering the input image with the template;

determining a position of the target region based on the registering; and

gating a medical procedure based on the determined position of the target region.

- 50. (Original) The method of claim 49, further comprising enhancing a moving object in the input image.
- 51. (Original) The method of claim 50, wherein the enhancing comprises subtracting an average of previously acquired input images from the input image.
- 52. (Original) The method of claim 49, wherein the registering comprises selecting the template from a plurality of templates that best matches an image in the input image.
- 53. (Original) The method of claim 52, wherein the determining the position of the target region comprises determining a position of the image in the input image that best matches with the template.
- 54. (Original) The method of claim 49, wherein the medical procedure comprises a radiation treatment, and the gating comprises activating or deactivating a radiation beam based on the determined position of the target region.
- 55. (Original) A system for performing physiological gating in a medical procedure, comprising:

means for providing a template;

means for acquiring an input image of a target region;

means for registering the input image with the template;

means for determining a position of the target region based on the registering; and means for gating a medical procedure based on the determined position of the target region.

- 56. (Original) The system of claim 55, wherein the means for registering comprises means for selecting the template from a plurality of templates that best matches an image in the input image.
- 57. (Original) The system of claim 55, wherein the medical procedure comprises a radiation treatment, and the means for gating comprises means for activating or deactivating a radiation beam based on the determined position of the target region.
- 58. (Original) A computer readable medium having a set of stored instructions, the execution of which causes a process to be performed, the process comprising:

providing a template;

acquiring an input image of a target region;

registering the input image with the template;

determining a position of the target region based on the registering; and

gating a medical procedure based on the determined position of the target region.

- 59. (Original) The computer readable medium of claim 58, wherein the process further comprising enhancing a moving object in the input image.
- 60. (Original) The computer readable medium of claim 59, wherein the enhancing comprises subtracting an average of previously acquired input images from the input image.
- 61. (Original) The computer readable medium of claim 58, wherein the registering comprises selecting the template from a plurality of templates that best matches an image in the input image.
- 62. (Original) The computer readable medium of claim 58, wherein the determining the position of the target region comprises determining a position of the image in the input image that best matches with the template.
- 63. (Original) The computer readable medium of claim 58, wherein the medical procedure comprises a radiation treatment, and the gating comprises activating or deactivating a radiation beam based on the determined position of the target region.
- 64. (Previously Presented) The method of claim 1, wherein the act of acquiring the sequence of images is performed during a treatment session.

- 65. (Previously Presented) The system of claim 10, wherein the means for acquiring the sequence of images is configured to acquire the sequence of images during a treatment session.
- 66. (Previously Presented) The computer readable medium of claim 15, wherein the act of acquiring the sequence of images is performed during a treatment session.